



# TOB-I2000 Infusion Pump

## Feature & Functions:

### Compact design

The compact and light weight design saves space and is beneficial during patient transfer  
Large & colorful LCD display

### Added safety

#### Free flow protection

The built-in flow stop feature helps reduce the risk of accidental free flow when pump door is open.

#### Anti-bolus function

Diminishes the volume of unwanted Bolus injected to the patient after removal of the occlusion cause.

Anti-reverse rotation detection

#### Panel Lock

The panel lock feature helps prevent unauthorized changes of any instrument setting

### Versatile functions

1600 history records

Real time display

RS232 interface

90° rotatable pole clamp convenient for horizontal bar, vertical IV pole & platform use

### User-friendly operation

Soft key design, easy to operate

Load directly the last infusion rate and volume limit

Adjustable buzzer volume

Top indicator light reflects the operation status as well as alarm case

Night mode to ensure good rest of patients

Removable pump body for easy cleaning



**Free flow protection**




**RS232 interface**

1600 event logs and alarm information can be transferred to computer for review



**90° rotatable pole clamp**

Fixation on vertical pole or horizontal bar



**Removable pump body**

convenient for cleaning

## TOB-I2000 Infusion Pump Specification

Specification		
Infusion mode	Rate mode	Drip mode
Flow rate range	0.1~1200 ml/h	Micro mode: 0.1-99.9 ml/hr in 0.1 ml increments
Volume to be infused (VTBI)	0~9999ml	
Volume Infused (Σ)	0 ~36000 ml	
Infusion accuracy	± 5%	
Applicable infusion set	Support a wide variety brands of infusion set including major manufacturers & selected local brands	
KVO rate	1 ~ 5 ml/h	
Bolus rate	300 ~ 1200 ml/h	
Purge	600ml/h	
Air bubble detection	Ultrasound sensor detection with four levels of air in line alarm adjustable	
Occlusion pressure	3 adjustable occlusion pressure settings: low, middle and high	
Alarms	Visual and audible alarms:Door open,Air-In-Line, Occlusion,Infusion completion, infusion near over, Start reminder function, Low Battery,Battery depleted,malfunction etc.	
Computer Interface	RS232 (optional)	
History records	1600 history records	
Power supply	AC:100~240V,50/60Hz DC:12V ±1V	
Battery	Rechargeable lithium polymer battery,7.4V,1900mAh Can operate up to 6 hours after fully charged at 25ml/h.	
Battery recharge time	10h with power on, 3h with power off	
Power consumption	25VA	
Classification	Class I, type CF	
Waterproof Level	IPX3	
Mode of operation	continuous	
Dimensions		
weight	≤1.4kg	
Operating conditions	Temperature:5°~40°,relative humidity:10~95%, Atmosphere pressure:86~106kPa	
Transport conditions	Temperature-20°~+60°,relative humidity:10~95%, Atmosphere pressure:50~106kPa	
Storage conditions	Temperature-20°~+45°,relative humidity:10~95%, Atmosphere pressure:50~106kPa	



**Oxford Medical Group Inc.**

**869 E. Schaumburg Rd. Suite 194**

**Schaumburg, IL 60194 / USA**

**Phone: +630-847-0744 / E-mail: sales@oxford.com**